


OUTLINE

Lens Specifications - NMV - 25			
Specifications	Value	1/2"	1/3"
Focal Length	$f = 25\text{mm}$		
Maximum diameter (Ratio)	$F = 1.4:1 \sim 16 \sim \text{Close}$		
Picture Size	12.8 x 9.6mm	8.8 x 6.6mm	6.4 x 4.8mm
Angle - Vertical	22.0 deg.	15.1deg.	11.0 deg.
Horizontal	29.3deg.	20.2 deg.	14.7deg.
Diagonal	36.6 deg.	25.2deg	18.3 deg.
Distortion (TV)	-1.0%	-0.5%	-0.3%
Minimum Focus Distance	0.3m		
Flange Back	17.526mm in air		
Back Focus	16.5mm in air		
Filter Screw Size	M35.5 x 0.5		
Effective Diameter - Front	21.0mm dia.		
- Rear	19.4mm dia.		
Mount	C-Mount		
Exit Pupil	-57.8mm dia.		
Temperature Range	- 10 ~ + 45 deg. C		
Strong Temperature Range	- 40 ~ + 60 deg. C		

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES AND INCLUDE CHEMICALLY APPLIED OR PLATED FINISHES	
SCALE:	1.5:1
WEIGHT:	See Table
DR:	BE
CH:	
PROJECT #:	E2338
DATE DR:	7/13/2007

THE CONTENTS OF THIS DOCUMENT ARE PROPRIETARY TO NAVITAR, ITS USE IS AUTHORIZED ONLY FOR RESPONDING TO REQUEST FOR QUOTATION OR PERFORMANCE OF WORK FOR NAVITAR	
0.0	1.0
inch	
0.0	25.0
mm	
DO NOT SCALE DRAWING	

 ROCHESTER, NEW YORK	
LENS, 25.0mm FL, , 1.0", f/1.4	
SIZE	B
	NMV - 25M1
REV	A
SHEET 1 OF 1	